

Roofing Solutions: *Why Use a System - Quality Shingles*



“Popular Choice For A Classic Wood Shake Look”

The unique "Shadow Accent" effect results in maximum dimensionality and depth!

(Featured nationwide except the Northeast)



Click image above to view Timberline 40 Shadow Accent shingles on a house.

In the Northeast only, Timberline Select 40™ Shingles are produced with the unique "Color Tones" look, which results in a more highly contrasted appearance.



Click image above to view Timberline 40 Color Tones shingles on a house.

for HOMEOWNERS

- **Popular Choice...** Timberline® Select 40™ Shingles are 17% heavier and thicker*, promoting longer life and extended durability.
- **Fantastic Appearance...** Featuring the distinctive Shadow Accent™ effect, resulting in a classic wood shake appearance.
- **Safer...** Class A fire and wind ratings from Underwriters Laboratories — the highest ratings possible.
- **High Performance...** Heavyweight design and extra-strong Micro Weave® Core make it a popular choice in the Timberline® Series—America’s most popular architectural shingles!
- **Stays In Place...** Dura Grip® adhesive seals each shingle tightly and reduces the risk of shingle blow-off. Shingles confidently warranted to withstand winds up to 80 mph!**
- **Peace Of Mind...** 40-year ltd. transferable warranty with Smart Choice® Protection for the first five years (non-prorated material and installation labor coverage).**
- **Perfect Finishing Touch...** Use distinctive TIMBERTEX® Ridge Cap shingles (in the West, use PacificRIDGE™ or Universal Ridge Cap Shingles; in the Southeast, use Universal Ridge Cap Shingles)

for PROFESSIONALS

- **More Referrals...** People will know that you’re installing America’s #1-selling laminated shingles!
- **Less Chance Of Call-Backs...** Durable, wind resistant shingle offers superior (80 mph) ltd. wind warranty!**

*Versus Timberline® 30 shingles

** See ltd. warranty for complete coverage and restrictions

Specifications for Timberline Select 40™

- Heavyweight Design
- 40-Year Ltd. Transferable Warranty
- Smart Choice® Protection for the first 5 years
- 80 mph Ltd. Wind Warranty
- Fiberglass Asphalt Shingle
- Listed Class A Fire-UL 790
- Passes UL 997 Wind Test
- Passes 110 mph Wind Test
- Algae-Eater™ Protection available in certain areas (check sample board for details)
- CSA A123.5-98
- ASTM D7158, Class H
- ASTM D3018 Type 1
- ASTM D3161 Type 1
- ASTM D3462*
- Dade County Approved (select plants)
- Meets Wisconsin Administrative Code
- Texas Department Of Insurance
- Approx. 64 Pieces/Square (Metric)
- Approx. 78 Pieces/Square (English)
- 4 Bundles/Square
- Approx. 256 Nails/Square (Metric)
- Approx. 312 Nails/Square (English)
- 5 5/8" Exposure (Metric)
- 5" Exposure (English)

*Product is manufactured to meet or exceed ASTM D3462; values from subsequent testing may vary depending on storage conditions.

For Distinctive Ridge Cap Shingles, use matching TIMBERTEX® or PacificRIDGE™ Ridge Cap Shingles



Applies to
Timberline Select 40
White Shingles Only.



*Timberline® Select 40™
shingles are available
nationwide*