

# Roofing Systems

## Polyglass USA Inc

1111 W Newport Center Dr  
Deerfield Beach, FL 33442 United States

R25992

## OTHER SYSTEMS

### Class A

#### 1. Deleted

#### 2. Deck: NC

**Incline:** Unlimited

**Insulation:** — Any UL Classified polyisocyanurate, any thickness.

**Base Sheet:** — One ply "Polystick MTS", "Polystick MTS Plus" "Polystick MU-X", or "Polystick XFR" (self-adhered), or "PolyAnchor UDL 40" mechanically fastened.

**Surfacing:** — Any UL Listed or Classified copper panels or UL Listed or Classified steel standing seam panels, stone coated shingles, 26 gauge minimum.

#### 3. Deck: C-15/32 or spaced sheathing

**Incline:** Unlimited

**Impact:** 4

**Base Sheet (optional):** — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X" self-adhered.

**Underlayment:** — One ply "Polystick XFR" self-adhered.

**Insulation (optional):** — "Polytherm" or "Polytherm-H" or any UL Classified polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness mechanically fastened or adhered with any UL Classified insulation adhesive.

**Ply Sheet (optional):** — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X" self-adhered.

**Surfacing:** — Any UL Listed or Classified copper panels or UL Listed or Classified steel standing seam panels stone coated shingles, 26 gauge minimum.

#### 4. Deck: C-15/32 or spaced sheathing

**Incline:** Unlimited

**Base Sheet (optional):** — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or "PolyAnchor UDL 40" mechanically fastened or "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X" self-adhered.

**Underlayment:** — Two plies "Polystick XFR" self-adhered.

**Insulation (optional):** — "Polytherm" or "Polytherm-H" or any UL Classified polyisocyanurate, perlite, wood fiber or polyisocyanurate/perlite board, any thickness mechanically fastened or adhered with any UL Classified insulation adhesive.

**Ply Sheet (optional):** — Minimum one ply Type 15 or Type 30 asphalt saturated felt or Type G1 or Type G2 asphalt saturated glass mat or "PolyAnchor UDL 40" mechanically fastened or "Polystick XFR", "Polystick MTS", "Polystick MTS Plus", "Polystick MU-X" self-adhered.

**Surfacing:** — Any UL Classified minimum 0.032 inches thick aluminum panels, mechanically fastened.