

Prepared Roof-covering Materials

COMPANY

GAF

1 Campus Dr
Parsippany, NJ 07054 United States

R21

Asphalt glass fiber mat shingles - "Royal Sovereign®", "Timberline® HD", "Timberline® Natural Shadow®", "Timberline® NS", "Timberline® Ultra HD", "Timberline® UHD", "Timberline® Cool Series®", "Timberline® American Harvest™", "[Timberline® HDZ™](#)", "Timberline® UHDZ™", "Timberline® Ultra HDZ™", "Timberline® AH", "Timberline® CS", "Fortitude™", "Timberline® ArmorShield™ II", "Timberline® AS II", "Timberline® Solar HD", "Timberline® Solar HDZ™", "Marquis WeatherMax®", "Grand Canyon®", "Grand Sequoia®", "Grand Sequoia® ArmorShield™", "Grand Sequoia® AS", "Camelot®", "Camelot® II", "Slateline®", "Woodland®", "Sienna®" or "Glenwood®" for installation as a [Class A](#) prepared roof covering. Suitable for installation on minimum 3/8-in. thick plywood roof decks in combination with a minimum of one ply of UL Certified prepared roofing accessory or UL Certified Type 15 or Type 30 felt. Also Classified in accordance with ASTM D3161/D3161M, Class F. Also Classified in accordance with ASTM D3462/D3462M. Also Classified in accordance with ICC ES AC438.

Asphalt glass fiber mat shingles - "Pro-Start™ Starter Strip Shingles" for installation as a Class A prepared roof covering. Suitable for installation on minimum 3/8-in. thick plywood roof decks in combination with a minimum of one ply of UL Certified prepared roofing accessory or UL Certified Type 15 or Type 30 felt. Also Classified in accordance with ASTM D3161/D3161M, Class F.

Asphalt glass fiber mat shingles - "WeatherBlocker™ Premium Eave/Rake Starter Strip Shingles" for installation as a Class A prepared roof covering. Suitable for installation on minimum 3/8-in. thick plywood roof decks in combination with a minimum of one ply of UL Certified prepared roofing accessory or UL Certified Type 15 or Type 30 felt. Also Classified in accordance with ASTM D3161/D3161M, Class F. Also Classified in accordance with ASTM D3462/D3462M.

Asphalt glass fiber mat shingles, "Royal Sovereign®", "Timberline® HD", "Timberline® Natural Shadow®", "Timberline® NS", "Timberline® Ultra HD", "Timberline® UHD", "Timberline® Cool Series®", "Timberline® American Harvest™", "Fortitude™", "Marquis WeatherMax®", "Grand Canyon®", "Grand Sequoia®" and "Camelot®" for installation as Class A prepared roof covering when used with minimum Type 30 underlayment over existing wood shingle roof.

Asphalt glass mat hip and ridge shingles- "Timbertex® Hip and Ridge" for installation as Class A prepared roof covering. Also been evaluated in accordance with ASTM D3161/D3161M, Class F when Henkel "PL Roofing and Flashing Sealant" or Sonneborn "NP1 Gun-Grade Polyurethane Sealant" is applied as specified in manufacturer's application instructions."

Asphalt glass mat hip and ridge shingles, "Z® Ridge Cap Shingles", "TimberCrest™ Premium SBS-Modified Ridge Cap Shingle", "TimberCrest® AS Premium SBS-Modified IR Ridge Cap Shingles", "TimberTex® Premium Ridge Cap Shingles", "Ridglass® Premium Ridge Cap Shingles", for installation as Class A prepared roof coverings. Also been evaluated in accordance with ASTM D3161/D3161M, Class A.

Asphalt glass mat hip and ridge shingles, "Z® Ridge Cap Shingles", "TimberTex® Premium Ridge Cap Shingles", for installation as Class A prepared roof coverings. Also been evaluated in accordance with ASTM D3161/D3161M, Class F when Henkel Corp. "Loctite PL Roof & Flashing Polyurethane Sealant" is applied as specified in manufacturer's installation instructions.

Asphalt glass mat hip and ridge shingles, "Seal-A-Ridge® Ridge Cap Shingles", "Seal-A-Ridge® ArmorShield™" and "Seal-A-Ridge® AS SBS-Modified IR Ridge Cap Shingles" for installation as Class A prepared roof coverings. Also been evaluated in accordance with ASTM D3161/D3161M, Class F.

Asphalt glass mat hip and ridge shingles, "TimberCrest™ Premium SBS-Modified Ridge Cap Shingle" or "TimberCrest® AS Premium SBS-Modified IR Ridge Cap Shingles" for installation as Class A prepared roof covering. Also been evaluated in accordance with ASTM D3161/D3161M, Class F when ASTM C920 Henkel "Loctite PL Roofing and Flashing Sealant" is applied as specified in manufacturer's installation instructions.

Last Updated on 2022-08-29

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."